



WP-871xr

4K HDR HDMI 1-Gang PoC Wall-Plate
Transmitter over Long-Reach DGKat 2.0

| HDMI | DGKat | 4K/60 UHD (4:4:4)



WP-871xr is a high-performance, long-reach DGKat™ 2.0 wall-plate transmitter for 4K@60Hz (4:4:4) HDR HDMI and HDCP 2.2 signals and power over twisted pair. It converts the HDMI input signal into a DGKat™ 2.0 signal and transmits it to a compatible receiver. WP-871xr extends the signal to up to 60m (200ft) at 4K@60Hz (4:4:4) resolution and up to 70m (230ft) at 4K@30Hz (4:4:4) 24bpp resolution over Kramer shielded cables. This wall-plate is powered through PoC (Power over Copper) over the twisted pair cable

FEATURES

High Performance Transmitter - Professional DGKat™ 2.0 transmitter for providing long-reach signals over twisted pair copper infrastructures. WP-871xr transmitter employs high-level video compression technology that delivers visually lossless performance for 4K@60Hz (4:4:4) HDR signals with near-zero latency. It converts the HDMI input signal into a DGKat™ 2.0 signal and transmits it to a compatible receiver

HDMI Signal Extension - HDR, HDCP 2.2 compliant. Supports deep color, x.v.Color™, lip sync, HDMI uncompressed audio channels, Dolby TrueHD, DTS-HD, 2K, 4K, and 3D as specified in HDMI 2.0

EDID Pass-through - Pass-through algorithm ensures Plug and Play operation for HDMI source and display systems

Multi-channel Audio Extension - Up to 32 channels of digital stereo uncompressed signals for supporting studio-grade surround sound

Cost-Effective Maintenance - Power and connectivity status LED indicator facilitates easy local maintenance and troubleshooting

Easy Installation - Compactly fits into standard US, EU and UK 1-gang in-wall box size, supporting decorative integration with room deployed user interfaces such as electrical switches. Wall-plate installation is fast and cost-effective via a single twisted pair cable, providing both video signal and power (PoC) connections



kramer

TECHNICAL SPECIFICATIONS

| | |
|----------------------------------|--|
| Inputs | 1 HDMI: On an HDMI female connector |
| Outputs | 1 DGKat: On an RJ-45 female connector |
| Video | Max Data Rate: 18Gbps (6Gbps per graphic channel) Max Resolution: 3840x2160@60Hz (4:4:4) 24bpp Standards Compliance: HDR10, HDCP 2.2 HDMI Support Deep color, x.v.Color™, lip sync, HDMI uncompressed audio channels, Dolby TrueHD, DTS-HD, 2K, 4K, and 3D as specified in HDMI 2.0 |
| High Compression Reach Extension | Using Shielded UNIKAT Cables Up to 60m (200ft) at 4K@60Hz (4:4:4), Up to 70m (230ft) at 4K@30Hz (4:4:4) or full HD (1080p @60Hz 36bpp) |
| Extension Line | Signal Compression: High compression level applied to >1080p signals Compliance: DGKat 2.0 |
| User Interface | Indicator: Power/connection Controls: Dip-switches to define compression setup |
| Power | Source: 12V DC, 2A Consumption: 600mA |
| Environmental Conditions | Operating Temperature: 0° to +40°C (32° to 104°F) Storage Temperature: -40° to +70°C (-40° to 158°F) Humidity: 10% to 90%, RHL non-condensing |
| Enclosure | Size: 1-gang Type: Aluminum Cooling: Convection ventilation |
| Accessories | Included: power adapter with cord, bracket set |
| STANDARDS COMPLIANCE | Safety: CE, UL Environmental: RoHs, WEEE |
| Product Dimensions | UK: 8.60cm x 3.10cm x 8.60cm (3.39" x 1.22" x 3.39") W, D, H EU: 8.00cm x 3.10cm x 8.00cm (3.15" x 1.22" x 3.15") W, D, H US: 6.98cm x 3.10cm x 11.43cm (2.75" x 1.22" x 4.50") W, D, H |
| Product Weight | UK: 0.1kg (0.1lbs) approx EU: 0.1kg (0.1lbs) approx US: 0.1kg (0.1lbs) approx |
| Shipping Dimensions | UK: 23.20cm x 13.60cm x 10.00cm (9.13" x 5.35" x 3.94") W, D, H EU: 23.20cm x 13.60cm x 10.00cm (9.13" x 5.35" x 3.94") W, D, H US: 23.20cm x 13.60cm x 10.00cm (9.13" x 5.35" x 3.94") W, D, H |

Shipping Weight

UK: 0.6kg (1.3lbs) approx

EU: 0.6kg (1.3lbs) approx

US: 0.6kg (1.2lbs) approx





CONFIGURATIONS

| | |
|----------------------|--|
| WP-871XR/US(W/B) | US-D-size Wall-Plate Transmitter, with White & Black Decora® Design Frame Sets |
| WP-871XR/EU-80/86(W) | EU & UK-size Wall-Plate Transmitter, with EU & UK White Frames |

