



kramer

C-GM/GF

15-pin HD to 15-pin HD Cables

| VGA/UXGA - 15-pin HD



Kramer's C-GM/GF computer graphics video cable is a high-performance cable with molded 15-pin HD connectors on both ends. It is used for connecting computer graphics video signals between computers or video scalars and plasma, LCD or other popular display technologies

FEATURES

Quality Construction - High-resolution 26 gauge mini coax for video

Easy Installation - Pre-terminated with molded 15-pin HD connectors, gold plated pins and thumbscrews for easy connection

Varied Selection of Lengths - Available in versions of 3 to 100ft (0.9 to 30.5m)

Cable Specs - See Kramer BC-3X2T7S for detailed cable specs



kramer

TECHNICAL SPECIFICATIONS

Attenuation (dB/100 ft.):	-0.5dB @1MHz.-1.3dB @5MHz.-1.9dB @10MHz.-4.0dB @50MHz.-5.7dB @100MHz.-8.0dB @180MHz.-14.0dB @400MHz
Conductor:	26 AWG 7/34 tinned copper 26 AWG 7/34 tinned copper
Dielectric:	Foam polyethylene with red, green, blue color coding 0.076in (1.95mm)
Shield:	(A) 90% spiral 38 AWG tinned copper.(B) aluminum-foil/Mylar 25% overlap rate (A) 85% braid 36 AWG tinned copper.(B) Mylar 25% overlap rate (A) 85% braid 36 AWG tinned copper.(B) aluminum-foil/Mylar 25% overlap rate
Inner Jacket:	PVC
Jacket Colors:	Black White, white/black, red, red/black Red, orange, brown, yellow, black, red/black
Center Conductor:	0.019in (0.48mm)
Individual Coax:	0.102in (2.6mm)
Impedance:	75Ω
DC resistance:	45Ω/1000ft (148Ω/km)
Capacitance:	17.3pF/ft (57pF/m)
Temperature:	68° to 167°F (-20° to 75°C)
Jacket:	HD polyethylene HD-polyethylene
Diameter:	0.34in (0.88mm) 0.34in (0.88mm)
Conductors:	26 AWG 7/34 tinned copper
Outer Jacket:	PVC
Outer Jacket Color:	Dark gray w/white lettering
Outer Diameter:	0.393in (10.0mm)
UL:	CL2
CSA:	C(UL) CL2



kramer

CONFIGURATIONS

C-GM/GF-3	Molded 15-pin HD (M) to 15-pin HD (F) Cable
C-GM/GF-6	Molded 15-pin HD (M) to 15-pin HD (F) Cable
C-GM/GF-10	Molded 15-pin HD (M) to 15-pin HD (F) Cable
C-GM/GF-15	Molded 15-pin HD (M) to 15-pin HD (F) Cable
C-GM/GF-25	Molded 15-pin HD (M) to 15-pin HD (F) Cable
C-GM/GF-35	Molded 15-pin HD (M) to 15-pin HD (F) Cable
C-GM/GF-50	Molded 15-pin HD (M) to 15-pin HD (F) Cable
C-GM/GF-75	Molded 15-pin HD (M) to 15-pin HD (F) Cable
C-GM/GF-100	Molded 15-pin HD (M) to 15-pin HD (F) Cable